

SUBMIT TO : Seventh Symposium on Integrated Observing Systems: The water cycle

Chair: Alexander E. McDonald

TITLE: System and Performance Analyses of Spaceborne Doppler Radars for Measuring Vertical Rainfall Velocity

AUTHOR LISTING:

Simone Tanelli Jet Propulsion Laboratory, California Institute of Technology
4800 Oak Grove Dr., Pasadena CA 91109, USA
Phone: +1 (818) 354 0195, Fax: +1 (818) 393 5285, E-mail:simone@radar-sci.jpl.nasa.gov

Eastwood Im Jet Propulsion Laboratory, California Institute of Technology
4800 Oak Grove Dr., Pasadena CA 91109, USA
Phone: +1 (818) 354 0492, Fax: +1 (818) 393 5285, E-mail:eastwood.im@jpl.nasa.gov

Stephen L. Durden Jet Propulsion Laboratory, California Institute of Technology
4800 Oak Grove Dr., Pasadena CA 91109, USA
Phone: +1 (818) 354 4719, Fax: +1 (818) 393 5285, E-mail:stephen.l.durden @jpl.nasa.gov

Luca Facheris Dipartimento di Elettronica e Telecomunicazioni, Univ. di Firenze,
Via di Santa Marta 3, Firenze 50139, Italy
Phone: +39 (055) 4796 274, Fax: +39 (055) 488 883, E-mail:facheris@ingfi1.ing.unifi.it

PRESENTATION: Oral Presentation

BRIEF BIOGRAPHY: Eastwood Im is the Supervisor of the Atmospheric Radar Science and Engineering Group at JPL, and the Radar Instrument Manager of the NASA's CloudSat Mission. He has extensive experience in spaceborne meteorological radar science and remote sensing, and advanced radar system studies. Dr. Im is the Principal Investigator on several NASA's atmospheric science and technology research tasks.

ABSTRACT TEXT:

Knowledge of the global distribution of the vertical velocity of precipitation is important in estimating latent heat fluxes, and therefore in the general study of energy transportation in the atmosphere. Such knowledge can only be acquired with the use of spaceborne Doppler precipitation radars. Although the high relative speed of the radar with respect to the rainfall particles introduces significant broadening in the Doppler spectrum, recent studies have proven that the average vertical velocity can be measured to acceptable accuracy levels by appropriate selection of radar parameters. Furthermore, methods to correct for specific errors arising from NUBF effects and pointing uncertainties have recently been developed.

In this paper we will present the results of the trade studies on the performances of a spaceborne Doppler radar with different system parameters configurations. Particular emphases will be placed on: 1) the choice of the PRF vs. antenna size ratio, 2) the choice of the observational strategy, 3) the choice of the operating frequency; and the 4) processing strategy. The results are generated from a 3D spaceborne Doppler radar simulator created using either the high resolution airborne Doppler radar rainfall datasets, or by a cloud resolving simulator. The results show that accuracies of 1 m/s or better can be achieved with the currently available technology and with careful selection the system parameters.

The research described in this paper was performed at the Jet Propulsion Laboratory, California Institute of Technology, for the TRMM and GPM Programs under contract with the National Aeronautics and Space Administration, and at the University of Firenze was through a program funded by the Italian Space Agency.

Keywords: Doppler, Spaceborne Radar, Precipitation